


1. Emergency stop button
2. Control panel
3. Main switch
4. Main power supply
5. Manual roller drive

## TECHNICAL DATA

C - MODEL	LR2510	LR2512	LR2514
Roller diameter	250 mm	250 mm	250 mm
Roller length	1000 mm	1200 mm	1400 mm
Unlimited variable speed	-	-	Standard
Roller speed	3,9 m/min	3,9 m/min	4,1 m/min
Capacity	12 kg/h	14 kg/h	18 kg/h
Equivalent sound power level	45 dB(A)	45 dB(A)	45 dB(A)
<b>ELECTRICAL SERVICE SPECIFICATIONS</b>			
Service voltage	3+PE+N 400V, 50Hz		
Safe-guarding	16 A	16A	16 A
Total input	5,18 kW	6,18 kW	7,18 kW
Heating elements	5 kW	6 kW	7 kW
Bed motor	0,18 kW	0,18 kW	0,18 kW
Cable entry	4 x 2,5 mm <sup>2</sup> Cu	4 x 2,5 mm <sup>2</sup> Cu	4 x 2,5 mm <sup>2</sup> Cu
<b>DIMENSIONS</b>			
Unpacked H x W x D (mm)	1000 x 1400 x 420	1000 x 1600 x 420	1000 x 1800 x 420
Created H x B x D (mm)	1150 x 1460 x 500	1113 x 1640 x 500	1150 x 1880 x 500
Weight - net	110 kg	118 kg	128 kg
- gross	124 kg	130 kg	150 kg
Created volume	0,84 m <sup>3</sup>	0,91 m <sup>3</sup>	1,08 m <sup>3</sup>

 <b>LAUNDRY SYSTEMS</b>	LR2510, 12,14	Date	10.2.03	No.	03-103-1.2
		Author	T.Ř.	Index	A
<b>IRONING MACHINE</b>					